



230V ~ 50Hz CE



Technical specifications

Voltage [V]	250
Fuse [A]	16
Length [M]	2.5 - 5.0
MiniPlug [IP] IP rating	44
Testing & acceptance	EN 60309-1, EN 60309-2



defa.com

MiniPlug Xtreme Connection cable 1,5mm2

Item no.: see below

MiniPlug Xtreme Connection cable 1,5mm2

DEFA MiniPlug Xtreme connection cable is adapted to DEFA MiniPlug inlet cable and gives a reliable and good connection from electricity outlets to the car. The MiniPlug Xtreme is more durable and is suitable for cold weather and rough treatment. Xtreme has a black cap to distinguish from the MiniPlug.

Only use original DEFA MiniPlug connection cable together with DEFA MiniPlug inlet cable and connect the DEFA MiniPlug connection cable only to an earthed power socket. Fit and install parts according to the enclosed usage & installation guide.

Use

Connect (A) to the DEFA MiniPlug inlet cable contact in the front of your vehicle. Make sure not to harm or damage the connection cable. Ensure not to damage the cable insulation by squeezing the cable under the hood or in the doorway. Keep the cap on when the cable is not in use.

Maintenance

Disconnect the cable. Apply some silicon spray on the MiniPlug contact terminals before and after the season and ensure that either the cable or cap is damaged.

Item no.:

460955	(2,5m). Weight: 309 gr. (22ex x 2,5m pr. assembly box)
460957	(5,0m). Weight: 535 gr. (12ex x 5,0m pr. assembly box)

Part of

DEFA MiniPlug connecting cable is a part of DEFA WarmUp, ComfortKit and different cable kits.

Approvals

DEFA AS is conforming to the requirements ISO 9001, ISO 14001 and ISO 45001. In addition to this, our engine heaters and cables are conforming to the requirements of IATF 16949.