




Olympia LED - LED Radar



Olympia LED PIR



Olympia LED - the best choice with focus on Energy efficiency and Environment

Description

The housing is made of glass-reinforced polyester, and the diffuser of opal acrylics. All electro components are mounted on a separate steel plate painted in white.

Olympia Radar OnOff

The microwave sensor turns on and off the light. Master do not control other Masters.

Olympia Radar MinMaxOff

Microwavesensor switching between full effect and a min-level of 10 % based upon pre-set level. After a further delay the light turns off. In addition the Off function may be deactivated, which gives a MinMax fitting.

Olympia PIR On/Off

Turns on when detection in the surroundings.

Olympia PIR MinMax

Change between lowest dimming level and full effect when detection.

Application areas

Kitchen, corridors, entrances, stairs, break-rooms and washing areas.

Mounting

Olympia is fitted for mounting direct in ceiling or on wall. When surface cabling use enclosed distance spacers.

Installation

Push in terminal block 5x2,5 mm². Cable entrance Ø 21mm from behind.


LED modul

Effect from fitting: 30 W
Colour temperatur: 3000 K
Luminous flux fitting: 2054 lm
Luminous efficiency fitting: 68 lm/W
Colour index Ra: 85
Colour tolerance MacAdam: 3
Expected life time L70B50: 50 000 hour
Ambient temperatur Ta: 25°C

Others

Olympia LED (114924) is dimmable (1-10V) and can be used as slave together with the MinMaxOff version.

Nummer	Type	Kuppel	Bestykning	Styring	Vekt (kg)
114924	Olympia LED	Opal	LED 830 30W	1-10V	1,4
115570	Olympia LED	Opal	LED 830 30W	DALI	1,5
114925	Olympia LED Radar	Opal	LED 830 30W	MinMaxOff	1,5
114926	Olympia LED Radar	Opal	LED 830 30W	OnOff	1,5
115177	Olympia LED PIR	Opal	LED 830 30W	MinMax	1,6
115175	Olympia LED PIR	Opal	LED 830 30W	OnOff	1,6



Reservation for misprinting or product changes.