



El - central

Item number: 717212

El - central

The el-central is moist resistant, but place and fit the el-central on a dry and suitable place on board. Let the connectors point downwards. The el-central can also be flush mounted.

The el-central got 1 DEFA PlugIn male inlet contact and 2 outlets. 1 PlugIn female contact for DEFA chargers etc. and 1 schuko contact for other electric accessories. All the connectors is placed on one side. The earth wire contact is connected to a "katode protected diode bridge" reducing the corrosion when conneted to shore power.

Installation

Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger. If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician.

Read the mounting and user guide carefully.

Maintenance

Check the earth-leakage circuit-breaker function within and after the season marine/boat).

Item number 717212

1 x DEFA PlugIn inlet
1 x DEFA PlugIn outlet
1 x Schuko outlet

Delivered in single packaging.

Specifications

Item number	717212
Voltage [VAC]	230 VAC
Current [A]	16
IP Rating [IP]	44
H/B/D [mm] (ex. connector)	175x120x90
Weight [kg]	0,92

DEFA AS is conforming to the requirements ISO 9001, ISO 14001 and ISO 45001.

In addition to this, our engine heaters and cables are conforming to the requirements of IATF 16949