



El - central

Item number: 719310

EI - central

The electrical central unit is moisture-resistant, but should still be installed in a dry place on board the vessel. Make sure the connectors point downwards.

All connections are located on the underside of the electrical central unit. There is one PlugIn inlet connector and two outlets: one PlugIn outlet for charging, etc., and another Schuko outlet for additional equipment. The grounding point is internally connected to a cathodically protected diode bridge, which reduces the risk of corrosion when connected to shore power.

Installation

Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the installation. If you are unfamiliar with electrical systems: consult DEFA, a dealer or licensed electrician. Read the installation and user guide carefully.

Maintenance

Always test the Residual Current Device (RCD) at the beginning and end of each boating season to ensure proper protection.

Item number 719310

1 x DEFA PlugIn inlet
1 x DEFA PlugIn outlet
1 x Schuko outlet

Delivered in single packaging.

Specifications

Item number	719310
Voltage [VAC]	230 VAC
Current [A]	16
IP Rating [IP]	44
H/B/D [mm] (ex. connector)	200*128*116
Weight [kg]	0,92



DEFA AS is conforming to the requirements of both SO 9001, ISO 14001 and ISO 45001. In addition to this, our engine heaters and cables are conforming to the requirements of IATF 16949.

719310 - E00 02122025 HG