



H = Height, W = Width, D = Depth



## MultiCharger 1x35

Item number: 708501

### MultiCharger 1x35

DEFA MultiCharger 1x35 is based on modern switchmode technology.

#### Installation

Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger. If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician. **Read the mounting and user guide carefully.**

#### Use

The charger can stand parallel current load up to 20A pr. channel from another user at the same time as it charge the battery. The charging voltage is temperature compensated with external sensor. The charger can be connected to a LED remote gauge.

#### LED

Green pulse - Charging, Green light - Fully charged, Red pulse - Error

#### Maintenance

The charger is maintenance free.

#### Technical specifications

Input voltage [VAC]	220-240
Operating temperature [°C]	-35/+50
Charging voltage* S1 [VDC]	14,4
Maintenance charging S2 [VDC]	13,5
Charging current [A]	35
Battery size, max [Ah]	600
IP rating [IP]	44
H/W/D [mm]	200x98x53
Weight [kg]	1,6
Certifications	EN60335-1, EN60335-2-29, EN55014-1, EN55014-2, EN61003-3/2

\* Temperature-compensated approx 5,0 mV/°C/cell. Ref. 25°C.

