



H

W

H = Height, W = Width, D = Depth



Technical specifications

Input voltage [VAC]	230
Rated power [W]	190
Operating temperature [°C]	-35/+50
Charging voltage* [VDC]	14,4
Maintenance charging [VDC]	13,6
Charging current [A]	12
Battery size, max [Ah]	150
IP rating [IP]	44
H/W/D [mm]	138x98x53
Weight [kg]	1
Protection class	1
Certifications	EN60335-1, EN60335-2-29, EN55014-1, EN55014-2, EN61003-3/2

* Temperature-compensated approx 5,0 mV/°C/cell. Ref. 25°C.



SCAN ME
defa.com

MultiCharger 1x12

Item number: 705200

MultiCharger 1x12

DEFA MultiCharger 1x12A is based on modern switch-mode technology. These chargers represent the latest technology within battery charging and will give the batteries optimum life.

It is well suited to battery sizes up to approx. 150Ah and can maintenance charge the battery for an unlimited time.

Installation

Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger. If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician. Read the mounting and user guide carefully.

Use

The charger can stand parallel current load up to 6A pr. channel from another user at the same time as it charge the battery. The charging voltage is temperature compensated with external sensor. The charger can be connected to a LED remote gauge.

LED

Green pulse - Charging, Green light - Fully charged, Red pulse - Error

Maintenance

The charger is maintenance free.

