



H

W

H = Height, W = Width, D = Depth



Technical specifications

Input voltage [VAC]	220-240
Operating temperature [°C]	-35/+50
Charging voltage* S1 [VDC]	14,4
Maintenance charging S2 [VDC]	13,5
Charging current [A]	2x35
Battery size, max [Ah]	2x600
IP rating [IP]	44
H/W/D [mm]	200x190x53
Weight [kg]	3,3
Protection class	1
Certifications	EN60335-1, EN60335-2-29, EN55014-1, EN55014-2, EN61003-3/2

* Temperature-compensated approx 5,0 mV/°C/cell. Ref. 25°C.



SCAN ME

defa.com

RescueCharger 2x35

Item number: 708506

RescueCharger 2x35

DEFA RescueCharger 2x35 is based on modern switchmode technology.

It is well suited to charge batteries up to approx. 2x600Ah and can maintenance charge the battery for an unlimited time.

Installation

Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger. If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician. Read the mounting and user guide carefully.

Use

The charger can stand parallel current load up to 20A pr. channel from another user at the same time as it charge the battery. The charging voltage is temperature compensated with external sensor. The charger can be connected to a LED remote gauge.

LED

Green pulse - Charging, Green light - Fully charged, Red pulse - Error

Maintenance

The charger is maintenance free.

