



120V~60Hz



Intertek  
4000182



## Free hanging cable

DEFA MiniPlug power connector (A) is to be fitted into the specially developed DEFA MiniPlug inlet cable connector who is made to be discrete integrated in the front of modern streamlined vehicles. (B): Main power plug (NEMA 5-15P).

Only use original MiniPlug connecting cable together with MiniPlug inlet cable and connect the MiniPlug connecting cable only to an earthed power socket. Fit and install parts according to the enclosed usage & installation guide.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

### Item no

#460937 (2.0m/6.56 ft) Weight: 276gr. (9.7 oz)

#460932 (4.0m/13.12 ft) Weight: 540gr. (19 oz)

### Assembly box

#460937 (2.0m/ 6.56 ft) 40pcs Weight: 11.2kg (24.7 lb)

#460932 (4.0m/13.12 ft) 28pcs Weight: 15.3kg (33.7 lb)

### Usage

Connect the DEFA MiniPlug (A) to the DEFA MiniPlug inlet cable contact in the front of your vehicle. Make sure not to harm or damage the DEFA MiniPlug connecting cable. Ensure not to damage the cable insulation by squeezing the cable under the hood or in the doorway.

Keep the cap on the MiniPlug contact when the cable is not in use.

### Maintenance

Disconnect the cable. Apply some silicon spray on the MiniPlug contact terminals under the cover (A) before and after the season and ensure that either the cable or cover is damaged.

### Technical specifications

Voltage [V]	120
Fuse [A]	15
Lenght [m]	2.0 - 4.0
Enclosure rating	TYPE 3R
Certifications	UL 817, Eleventh edition, Dated March 16, 2001, Rev: October 5, 2009. CSA C22.2 No 21, 1995/03/01, Ed:8, R2009

[www.defa.com](http://www.defa.com)