



230V~ 50Hz

Item number

DEFA no.: 411500-411599 and 412500-412599.
Weight: Varies depending on diameter and size.
Up to 25-pack. Varies with the size of the heater.

Part of

Engine pre-heaters are supplied separately because of special adapted solutions for a variety of engines and vehicles.

Installation

Install the heater according to the enclosed installation guide.
ONLY Install the heater on vehicles listed in the installation guide.
Installing DEFA heaters must only be executed by authorized garages.

Use

Normal usage - DEFA engine heaters is dimensioned for "normal usage". DEFA defines "normal usage" as; 3 connections for 3 hours pr. 24 hour based upon 150 users days a year (5 months a year).

Professional usage - It is necessary to make a yearly function control and if necessary install a new heater to obtain necessary extent of service on emergency vehicles or power supplies where the heater is connected more or less 24/7. This yearly service cost will not be covered by DEFA AS.

Pulse power - Some car parking areas are using interval (pulse) power timers turning the power On and Off several times per hour. Using DEFA engine heater in suchlike parking facilities will not be considered as "Normal use" and claims will be declined.



SafeStart 500 series

Characteristics: Special fastener
DEFA no: 501-599, 2501-2599

Several engine models have very different types of caps that are used instead of a frost plug in the coolant tank.

These heaters got a flange (A) which is identical to the original cap. The heater is fastened with bolts. A gasket or an O-ring is used to form the seal. There is also a heater available in this series which consists of a flat or head flange, and which is fastened with a holder.

Tests made on a medium size vehicle, shows that a 600W 100-serie heater will increase the coolant temperature approx 50°C related to the outdoor temperature when connected in 195 minutes at an outdoor temperature of -17°C or colder. After 195 minutes the system has achieved thermal balance. Longer heating time that 195 minutes at -17°C or colder is energy dissipation. For that reason we recommend you to use a timer. Please look at the product sheet for DEFA SmartStart™ or DEFA Futura.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

Technical specifications

Voltage [V]	230
Power [W]	550-1530
IP rating [IP]	44
Test and approval	EMKO-TUB(61)NO 293/91 EN 60335-1, EMKO-TSB(61) NO293A94

www.defa.com