



Cenit M



Cenit – LED downlight with high light output

Description

Recessed downlight developed based upon LED with high light quality. Body in steel, trim ring in diecast aluminium. Reflector in matt anodized aluminium giving high output. Micro prismatic shielding. White trimring RAL 9003.

Application areas

Corridor, common rooms, office, shop, hotel, restaurant, official environments etc.

Mounting

The fitting is mounted into the ceiling by fixing clips which are included. Cut-out 200-210mm.

Installation

The fitting is supplied plug & play, complete with 2,5m 3-pole cable and plug from driver. DALI version 2,5m 5-pole cable without plug from driver.

Others

Cenit is available in 130 lm/W versions on request. Support plate for recessing in soft ceiling tiles is available as accessories (590x300mm).

Fittings (pcs) each circuit

	10-B	10-C	16-B	16-C
19W	31	51	50	80
19W DALI	20	31	30	50
24W	15	24	24	40
24W DALI	18	31	30	50

Light source

Colour temperature	3000K - 4000K
Colour index	RA 80
Colour tolerance	MacAdams 3
UGR	< 19
Beam angle	70°
Expected life time	L90B20 100.000 h




Number	Type	Light source	lm fitting	lm/W	Control	Weight (kg)
124124	Cenit M	19W 3000K	2150	113	cl II	0,9
124126	Cenit M	19W 3000K	2150	113	DALI	0,9
124125	Cenit M	19W 4000K	2250	118	cl II	0,9
124127	Cenit M	19W 4000K	2250	118	DALI	0,9
124128	Cenit M	24W 3000K	2750	115	cl II	0,9
124130	Cenit M	24W 3000K	2750	115	DALI	0,9
124129	Cenit M	24W 4000K	2850	119	cl II	0,9
124131	Cenit M	24W 4000K	2850	119	DALI	0,9

Delivered with drive included

Accessories:

101987	Support plate soft ceilings	590x300mm
--------	-----------------------------	-----------



Support plate 590x300mm