


Elite asymmetrical - LED floodlight



Elite asym - 25% more efficient - several new versions



Description

Body in pressure die-cast aluminium with impact 5 mm flat glass. Powder painted in grey - RAL 7035, corrosion class C5. Elite is design to give maximum heat transmission and long lifetime. CLO - Constant Light Output as standard. The fitting gratify EN 62471 requirement for photo biological safety. 6kV Surge Protection Device is integrated.

Application areas

The plain design of the fitting makes Elite suitable in various application areas. By use of the wall fixing Elite is ideal for use as wall light around buildings and plants. Due to the asymmetrical floodlight optics the fitting is primary designed for intensive lighting of pedestrian crossing and lighting of parking lots and other outdoor areas. Ideal for use in combination with Elite Large and Elite Small in areas with the need for a mix of street lighting and flood lighting, giving the possibility to maintain a familiar design.

Mounting

The fixing bracket in die-cast aluminium, is reversible for mounting on arm or pole top Ø40-76mm, can be tilted in steps of 5°. As standard the fitting is supplied with cable 12m 2x2,5mm² length on Elite large.

On request

- NR - automatic Night Reduction
- 10kV Surge Protection Device
- Alternative effects and luminous flux
- Other cable lengths
- Can be delivered with all open light control systems

Colour index: Ra >70
 Colour tolerance: MacAdams 3
 Lifetime: 100 000h L90B10
 Weight: 11,3 kg
 Vind surface: 0,043 m²

System efficiency up till 165 lm/W.

Number	Type	Light source			Control
125983	Elite large Asym	48LED-17000lm	110W	730	
125982	Elite large Asym	48LED-17000lm	110W	730	2xZhaga
123910	Elite large Asym	48LED-18000lm	110W	740	
124220	Elite large Asym	48LED-18000lm	110W	740	2xZhaga

Accessories:

128901 10kV Surge Protection Device with LED indicator
 119012 Wall bracket - Ø48x200 mm - 10°



10kV Surge Protection Device with LED indicator