


# Elite Asym - LED floodlight




Elite - clean lines - functional expression - Nordic design



Elite small



Elite large



## Description

Body in pressure die-cast aluminium with impact 5 mm flat glass. Powder painted in grey - RAL 7035, corrosion class C5. Elite is design to give maximum heat transmission and long lifetime. CLO - Constant Light Output as standard. The fitting gratify EN 62471 requirement for photo biological safety. 6kV Surge Protection Device is integrated.

## Application areas

The plain design of the fitting makes Elite suitable in various application areas. By use of the wall fixing Elite is ideal for use as wall light around buildings and plants. Due to the asymmetrical floodlight optics the fitting is primary designed for intensive lighting of pedestrian crossing and lighting of parking lots and other outdoor areas. Ideal for use in combination with Elite Large and Elite Small in areas with the need for a mix of street lighting and flood lighting, giving the possibility to maintain a familiar design.

## Mounting

The fixing bracket in die-cast aluminium, is reversible for mounting on arm or pole top Ø40-76mm, can be tilted in steps of 5°. As standard the fitting is supplied with 2x2,5mm<sup>2</sup> cable, 12m length on large and 8m length on small.

## On request

- NR - automatic Night Reduction
- 10kV Surge Protection Device
- Alternative effects and luminous flux
- Other cable lengths or Wieland quick connector
- Can be delivered with all open light control systems

Colour index: Ra >70  
 Colour tolerance: MacAdams 3  
 Lifetime: 100 000h L90B10  
 Weight small / large: 6,0 kg / 11,3 kg  
 Vind surface small / large: 0,032 m<sup>2</sup> / 0,043 m<sup>2</sup>

System efficiency up till 165 lm/W.

Number	Type	Light source	Control	lm fitting	lm/W
122130	Elite small Asym	32LED-9000lm 56W	740	9141	161
123910	Elite large Asym	48LED-18000lm 110W	740	18176	165
124220	Elite large Asym 2xZhaga	48LED-18000lm 110W	740	18176	165
124537	Elite large Asym	48LED-18000lm 110W	740 NR	18176	165

NR = Automatic Night Reduction 50% 6 h, ~ hr 23-05

## Accessori

- 123925 10kV Surge Protection Device with LED indicator
- 122520 Photo-cell kit - twilight relay (for Ledge small only)
- 119012 Wall bracket - Ø48x200 mm - 10°



10kV Surge Protection Device with LED indicator