


## New generation



Elite - clean lines - functional expression - Nordic design  
New generation - 25% more efficient - several new versions

### Description

Body in pressure die-cast aluminium with impact 5 mm flat glass.  
Powder painted in grey - RAL 7035, corrosion class C5. Elite is design to give maximum heat transmission and long lifetime, with a plain surface without any visible cooling ribs.  
CLO - Constant Light Output as standard. The fitting gratify EN 62471 requirement for photo biological safety.  
6kV Surge Protection Device is integrated.

### Application areas

The plain design of the fitting makes Elite suitable in various application areas. By use of the wall fixing Elite is ideal for use as wall light around buildings and plants.  
Due to the street light optics the fitting is ideal for use along minor roads, tracks, foot and cycle paths and parking areas.

### Mounting

The fitting is supplied with 2x2,5mm<sup>2</sup> cable, 8m length, available on request. The fixing bracket in die-cast aluminium, is reversible for mounting on arm or pole top Ø40-76mm, can be tilted in steps of 5°.

### On request

- 10kV Surge Protection Device
- Alternative effects and luminous flux
- Other cable lengths or Wieland quick connector
- Adapted for all open light control systems
- Night reduction with other levels/time settings
- Photo-cell kit
- Zhaga connector

Colour index: 4000K RA >70  
3000K RA >80  
Lifetime: 100 000h L90B10  
Weight: 6 kg  
Vind surface: 0,032 m<sup>2</sup>

System efficiency up till 161 lm/W.

| DEFA nr. | Type        | Light source  | Control    | lm fitting | lm/W |
|----------|-------------|---------------|------------|------------|------|
| 123858   | Elite small | 8LED 1900 lm  | 15W 830    | 1870 lm    | 126  |
| 123590   | Elite small | 8LED 2100lm   | 15W 740    | 2215 lm    | 148  |
| 123859   | Elite small | 16LED 3700 lm | 28W 830    | 3702 lm    | 134  |
| 123860   | Elite small | 16LED 3700 lm | 28W 830 NR | 3702 lm    | 134  |
| 123610   | Elite small | 16LED 4000 lm | 28W 740    | 4397 lm    | 157  |
| 123560   | Elite small | 16LED 4000 lm | 28W 740 NR | 4397 lm    | 157  |
| 123861   | Elite small | 24LED 5600lm  | 41W 830    | 5573 lm    | 136  |
| 123862   | Elite small | 24LED 5600lm  | 41W 830 NR | 5573 lm    | 136  |
| 123620   | Elite small | 24LED 6000lm  | 41W 740    | 6606 lm    | 161  |
| 123630   | Elite small | 24LED 6000lm  | 41W 740 NR | 6606 lm    | 161  |
| 123670   | Elite small | 32LED 9000lm  | 56W 740    | 9042 lm    | 159  |
| 123680   | Elite small | 32LED 9000lm  | 56W 740 NR | 9042 lm    | 159  |

NR = Automatic Night Reduction 50%, ~ hr 23-05

### Accessories:

- 122520 Photo-cell kit - twilight relay
- 123925 10kV Surge Protection Device with LED indicator



Photo-cell kit



10kV Surge Protection Device with LED indicator