



W

H

H = Height, W= Width



Charge kit 24VDC 1x40A

Item number: 711152

Charge kit 24VDC 1x40A

Charge kit contains:

- 1 x 708400 MultiCharger 40A 24V battery charger
- 1 x 460939 MiniPlug inlet cable (2,0m)
- 1 x 460957 MiniPlug Xtreme connection cable (5,0m)

Weight: 6000 gram

All parts are also available as single products.

The kit can be extended with a LED indicator for remote reading of charging status and possibly be connected to another charger or engine heater.

Installation

Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger. If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician.

Read the mounting and user guide carefully.

Technical specifications- 7008400

Mains voltage 220-240 V AC	220-240 V AC
Mains frequency 50/60 Hz	50/60 Hz
Mains current max. 5.9 A eff.	max. 5.9 A eff.
Efficiency max. 95 %	max. 95 %
Effective power max. 1224 W	max. 1224 W
Protection class I	I
EMC emission Class A	Klasse A
Output voltage range 4-30.6 V DC	4-30.6 V DC
Output current 40 A at 28.8 V DC	40 A ved 28.8 V DC
Battery return current < 1 mA	< 1 mA
Cooling Convection	Konveksjon
Dimensions (H, W, D) 280 x 175 x 85 mm	280 x 175 x 85 mm
Weight (without cable) 4.8 kg	4.8 kg
AC Power cable length 1 m	1 m
DC charging cable length 2 m	2 m
Operating temperature -35°C - +40°C	-35°C - +40°C
Storage temperature -40°C - +85°C	-40°C - +85°C
Climate class B	B
Degree of protection IP67	IP67
Standards	EN 60335-1, EN 60335-2-29, EN 61000-6-2 (EN 61000-4-2, EN 61000-4-3, EN 61000-4-4) (EN 61000-4-5, EN 61000-4-6, EN 61000-4-11), EN 61000-6-4 (Class A)

* Temperature-compensated approx 5,0 mV/°C/cell. Ref. 25 °C.