



120V~60Hz

W = Width, D = Depth, H = Height

## Termini™ 1200

DEFA Termini™ 1200 utilise a PTC heating element (PTC = Positive Temperature Coefficient). As the interior temperature rises, power output is reduced and thus power consumption as well.

The interior heater is equipped with an automatic overheating circuit breaker. This breaker is tripped at 55°C (131F), and it is reset by disconnecting the plug and leaving the interior heater switched off until it cools down (after approx. 30 minutes). There is also a lead fuse for additional protection. If this fuse blows, the interior heater must be sent to the factory for repair.

DEFA AS is conforming to the requirements ISO 9001, ISO 14001 and ISO 45001. In addition to this, our engine heaters and cables are conforming to the requirements of IATF 16949.

### Technical specifications

Voltage [V]	120
Rated power [W]	1200
Power [W] -25°C (-13°F)	1200
Power [W] +25°C (77°F)	900
W/H/D [mm]	138/182/36
Weight (average) [gram] (oz)	700 (24.7)
Enclosure rating	TYPE 1
Certifications	UL Std. No. 2021 CSA std. C22.2 No.46

### Item number

# 433103 (Termini plug)

Weight: 678 gr. (23.9 oz)

### Assembly box

# 433103 (Termini plug)

12pcs Weight: 8.6kg (19 lb)

### Usage & Installation

The interior heater is mounted in the interior of the vehicle with special holders. Termini™ can be mounted upside down under the glove compartment, on the centre console or on the A-pillar according to the enclosed mounting instruction.

**Install the interior heater according to the enclosed installation guide.**